ELSEVIER

Nuclear Engineering and Design 149 (1994) xiii–xiv

Nuclear Engineering and Design

## Contents of Volume 149

### Selected papers from the Sixth International Topical Meeting on Nuclear Reactor Thermal-Hydraulics, October 5–8, 1993, Grenoble, France

Preface, *R.T. Lahey, Jr.* ix

Foreword, *M. Courtaud and J.M. Delhaye* xi

The important role of thermal hydraulics in 50 years of nuclear power applications, *S. Levy* 1

Reasons for the occurrence of spurious solutions in two-phase flow codes, *Z. Bilicki and J. Kestin* 11

Critical flow and spurious solutions. Part I. The case of a single equation, *Z. Bilicki and J. Kestin* 17

Critical flow and spurious solutions. Part II. The case of *n* equations, *Z. Bilicki and J. Kestin* 29

The measurement of void waves in bubbly two-phase flows, *J.-W. Park, D.A. Drew and R.T. Lahey, Jr.* 37

Spatio–temporal complexities and chaos in a two-phase flashing flow, *M. Rajković, J.R. Riznić and M. Ishii* 53

Dynamic model for the interfacial shear as a closure law in two-fluid models, *N. Brauner and D. Moalem Maron* 67

Interfacial measurements in horizontal stratified flow patterns, *J. Shi and G. Koca-mustafaogullari* 81

Transient boiling heat transfer from initial steady state caused by rapid depressurization, *K. Fukuda, M. Shiotsu, K. Hata and A. Sakurai* 97

Identification of flow patterns of two-phase flow by mathematical modelling, *Z. Lu and X. Zhang* 111

Assessment of the CATHARE 1D pump model, *G. Geffraye and D. Bestion* 117

Analysis of UPTF downcomer tests with the CATHARE multidimensional model, *I. Dor* 129

The top-down reflooding model in the CATHARE code, *J. Bartak, D. Bestion and T. Haapalehto* 141

Multidimensional two-phase flow regime distribution in a PWR downcomer during an LBLOCA refill phase, *W.M. Dempster and D.S. Abouhadra* 153

A comparison of critical heat flux in tubes and annuli, *S. Doerffer, D.C. Groeneveld, S.C. Cheng and K.F. Rudzinski* 167

Analysis of critical heat flux during subcooled boiling for finned fuel elements, *J.E. Kowalski, J.R. Buell and T.V. Tran* 177

Critical heat flux data in a vertical tube at low and medium pressures, *A. Teyssedou, A. Olekhnowitch, A. Tapucu, P. Champagne and D. Groeneveld* 185

Critical heat flux experiments under steady-state and transient conditions and visualization of CHF phenomenon with neutron radiography, *T. Iwamura, H. Watanabe and Y. Murao* 195

An investigation of the constitutive relations for intersubchannel transfer mechanisms in horizontal flows as applied in the ASSERT-4 subchannel code, *P. Tye, A. Teyssedou and A. Tapucu* 207
The effect of turbulent mixing models on the predictions of subchannel codes, *A. Tapucu, A. Teyssedou, P. Tye and N. Troche* 221
The effect of grid assembly mixing vanes on critical heat flux values and azimuthal location in fuel assemblies, *F. de Crécy* 233
A new approach to the MDNBR concept, *F. de Crécy* 243
Optimisation of the operating conditions of pressurised water reactors limited by the DNB phenomenon, *M. Stievenart, W. Lodewijckx and J. Robeyns* 251
Turbulent heat transfer in a flat channel with stable and unstable stratification in the flow, *J. Vilemas, P. Poškas and J.E. Adomaitis* 261
Flow instabilities in boiling channels of pressure-tube-type reactor, *H. Mochizuki* 269
Fluid–structure coupling between a vibrating cylinder and a narrow annular flow, *L. Perotin* 279
Reflux condenser mode with non-condensible gas: assessment of Cathare against Bethsy test 7.2C, *B. Noel and R. Deruaz* 291
Investigation of fluid mixing with direct vessel injection, *J.H. Cha and H.G. Jun* 299
Effect of non-condensable gas and wavy interface on the condensation heat transfer in a nearly horizontal plate, *H.C. Kang and M.H. Kim* 313
Pressure drop, void fraction and shear stress measurements in an adiabatic two-phase flow in a coiled tube, *V. Czop, D. Barbier and S. Dong* 323
UPTF experiment refined PWR LOCA thermal-hydraulic scenarios: conclusions from a full-scale experimental program, *P. Weiss, R. Emmerling, R. Hertlein and J. Liebert* 335
The newest two-phase flow control devices in LWR equipment based on ultrasonic and WAT-technology, *V.I. Melnikov and B.I. Nigmatulin* 349
The adjoint sensitivity method, a contribution to the code uncertainty evaluation, *A. Ounsy, B. Brun and F. de Crécy* 357
Loss of residual heat removal during mid-loop operation: BETHSY experiments, *D. Dumont, G. Lavialle, B. Noel and R. Deruaz* 365
Development of a high speed particle image velocimetry technique using fluorescent tracers to study steam bubble collapse, *O.G. Philip, W.D. Schmidl and Y.A. Hassan* 375
Thermal-hydraulic analysis of the pellet bed reactor for nuclear thermal propulsion, *N.J. Morley and M.S. El-Genk* 387
Heat flux distribution from a volumetrically heated pool with high Rayleigh number, *O. Kymäläinen, H. Tuomisto, O. Hongisto and T.G. Theofanous* 401
Development of a multidimensional model for the premixing phase of a fuel–coolant interaction, *G. Berthoud and M. Valette* 409
Modeling of the breakup of melt jets in liquids for LWR safety analysis, *E.v. Berg, M. Bürger, S.H. Cho and A. Schatz* 419
Minimization of the effect of errors in approximate radiation view factors, *R. Clarksean and C. Solbrig* 431
Design considerations for the rotating electrostatic liquid-film radiator, *S.G. Bankoff, M.J. Miksis, H. Kim and R. Gwinner* 441
Fast and accurate water and steam properties programs for two-phase flow calculations, *W.C. Müller* 449
Pseudo-cubic thin-plate-type spline method for analysing experimental data, *F. de Crécy* 459
Author Index 467
Instructions to Contributors 471